

# SUPPLIES AND RECOMMENDED TOOLS

## SUPPLIES

### FASTENERS

#12 STAINLESS STEEL FASTENERS AS REQUIRED  
FOR PROPER SUBSTRAT ATTACHMENT

### SHIMS

1/16", 1/8" AND 1/4" HORSESHOE SHIMS

### SPACERS

1/4" HORSESHOE SHIMS

### SILICONE JOINT SEALANT

SUCH AS DOW CORNING 790  
OR  
PORTLAND-BASED GROUT

### OPTIONAL:

GREASELESS LUBRICANT SUCH AS LPS 1

## RECOMMENDED TOOLS

### LAYOUT:

SQUARES, LEVELS, TAPE MEASURES, CHALK AND STRING LINES,  
MISCELLANEOUS HAND TOOLS

### ATTACHEMENT OF ANCHORS:

3/8" DRILL WITH ASSORTED BITS (1/4"+) AND PHILLIPS DRIVER HEADS

### CUTTING ANCHORS:

ELECTRIC "CHOP SAW" OR EQUIVALENT

### CUTTING PANELS AND KERFS:

CIRCULAR SAW WITH DIAMOND MASONRY BLADE OR WET MASONRY SAW

### DRESSING AND CLEANING STONE:

60 GRIT WET-DRY SANDPAPER, STIFF BRISTLE BRUSH AND CLEAN WATER  
AND NON-ACIDIC LIGHT DETERGENT IF DESIRED

### CAULKING OR GROUTING JOINTS:

STANDARD CAULKING OR GROUTING TOOLS

**AMERICAN LIMESTONE COMPANY**

A TEXAS CORPORATION  
WWW.AMERICANLIMESTONE.COM  
INFO@AMERICANLIMESTONE.COM

INSTALLATION – SUPPLIES & RECOMMENDED TOOLS

**3.2.1**