

# AMERICAN LIMESTONE COMPANY

---

## DESIGNING WITH NATURAL LIMESTONE USING THE ALC SOLUTION

Ninth Edition  
May 2012

Also Available in  
AutoCad Format

Engineering:  
CDC, Inc.  
Curtain Wall Design and Consulting

ALL SCALES AND DIMENSIONS  
SHOULD BE CHECKED

©Copyright 1995  
American Limestone Company  
All Rights Reserved. United States Patents issued.  
January 1995

# AMERICAN LIMESTONE COMPANY

## DESIGNING WITH NATURAL LIMESTONE USING THE ALC SOLUTION

### TABLE OF CONTENTS

#### CHAPTER 1. – ALC SOLUTION APPLICATION EXAMPLES

##### 1.1 – CLASSICAL

- 1.1.1 TUSCAN ELEVATION
- 1.1.2 TUSCAN COLUMN WITH ARCH AND ENTABLATURE  
PHOTO OF TUSCAN COLUMN WITH ARCH AND ENTABLATURE
- 1.1.3 PLAN VIEW OF COLUMN AND PILASTER
- 1.1.4 TUSCAN PILASTER WITH PEDESTAL
- 1.1.5A SIDE VIEW OF TUSCAN COLUMN  
PHOTO OF TUSCAN COLUMN
- 1.1.5B ELEVATIONS OF TUSCAN PILASTER
- 1.1.6 IONIC COLUMNS WITH BALUSTRADE AND ENTABLATURE
- 1.1.7 IONIC PILASTER WITH FLUTING
- 1.1.8 IONIC PILASTER WITH ARCH AND PEDIMENT
- 1.1.9 IONIC PILASTER WITH CROSS SECTION AND EXTERIOR VIEW
- 1.1.10 IONIC COLUMN – SQUARE

##### 1.2 – LOAD BEARING MASONRY

- 1.2.1 LOAD BEARING MASONRY
- 1.2.2 LOAD BEARING MASONRY (CONTINUED)

##### 1.3 – PERIMETER WALLS

- 1.3.1 LIMESTONE BLOCK WALLS

#### CHAPTER 2. – ALC SOLUTION STANDARD ELEMENTS

##### 2.1 – QUOIN PANELS (SEE ALSO 2.6.6, 2.6.7 & 3.1.16–18)

- 2.1.1 QUOINED CORNER DETAIL – USING  
QUOINS 120, 121, 122 AND 123  
PHOTOS OF QUOINED CORNER AND QUOIN 126
- 2.1.2 TUSCAN ELEVATION – USING QUOIN 126
- 2.1.3 QUOIN 126

##### 2.2 – KEYSTONES

- 2.2.1 STANDARD KEYSTONE 1 WITH PROFILE 201-I SHOWN
- 2.2.2 STANDARD KEYSTONE 2 WITH PROFILE 301-T-B SHOWN

- 2.3 – ALC SOLUTION FIREPLACE SURROUNDS
  - 2.3.1 DESIGN YOUR OWN SURROUND USING STANDARD PROFILES
- 2.4 – ALC SOLUTION STANDARD MOLDINGS AND CARVINGS
  - 2.4.1 STANDARD PROFILES – THUMBNAILED 1
  - 2.4.1A STANDARD PROFILES – THUMBNAILED 2
  - 2.4.1B STANDARD PROFILES – THUMBNAILED 3
  - 2.4.1C STANDARD PROFILES – THUMBNAILED 4
  - 2.4.2 PROFILE 220–T TUSCAN
  - 2.4.3 PROFILE 301–T TUSCAN
  - 2.4.4 PROFILE 310–T TUSCAN
  - 2.4.5 PROFILE 320–T TUSCAN
  - 2.4.6 PROFILE 321–T TUSCAN
  - 2.4.7 PROFILE 323–T TUSCAN
  - 2.4.8 PROFILE 330–T TUSCAN
  - 2.4.9 PROFILE 401–T TUSCAN
  - 2.4.10 PROFILE 402–T TUSCAN
  - 2.4.11 PROFILE 201–I IONIC
  - 2.4.12 PROFILE 801–I IONIC
  - 2.4.13 PROFILE 810–I IONIC
  - 2.4.14 PROFILE 820–I IONIC
  - 2.4.15 PROFILE 830–I IONIC
  - 2.4.16 PROFILE 840–I IONIC
  - 2.4.17 PROFILE 850–I IONIC
  - 2.4.18 PROFILE 880–I IONIC
  - 2.4.19 PROFILE 701–G GOTHIC
  - 2.4.20 PROFILE 702–G GOTHIC
  - 2.4.21 PROFILE 230–M MISCELLANEOUS
  - 2.4.22 PROFILE 250–M MISCELLANEOUS
  - 2.4.23 PROFILE 901–M MISCELLANEOUS
  - 2.4.24 CAPITAL 890–I IONIC CAPITAL (FOR PILASTER)
  - 2.4.25 PROFILE 906–M MISCELLANEOUS
  - 2.4.26 PROFILE 907–M MISCELLANEOUS
  - 2.4.27 PROFILE 840–B IONIC (BRICK COMPATIBLE)
  - 2.4.28 PROFILE 701–B GOTHIC (BRICK COMPATIBLE)
  - 2.4.29 PROFILE 201–B IONIC (BRICK COMPATIBLE)
  - 2.4.30 PROFILE 702–B GOTHIC (BRICK COMPATIBLE)
  - 2.4.31 PROFILE 220–B TUSCAN (BRICK COMPATIBLE)
  - 2.4.32 PROFILE 202–M MISCELLANEOUS
  - 2.4.33 PROFILE 801–BR IONIC (FOR BALUSTRADE)
  - 2.4.34 PROFILE 850–HRC IONIC (FOR BALUSTRADE)

2.5 – ALC SOLUTION DOOR AND WINDOW APPLICATIONS

2.5.1 CURVED PROFILES

2.5.2 FLAT ARCHED WINDOW SURROUND WITH PROFILE 201-I

2.5.3 FLAT ARCHED WINDOW SURROUND WITH KEYSTONE 1

2.5.4 ARCHED WINDOW SURROUND

2.5.5 OCULUS WINDOW SURROUND WITH PROFILE 201-I AND KEYSTONE 1

2.5.6 ELLIPSE WINDOW SURROUND WITH PROFILE 201-I

2.6 – ALC SOLUTION CLADDING/STANDARD PANELS

2.6.1 PANEL 101

PHOTOS OF PANELS 101 & 150 AND THRU-PANEL CORNER

2.6.2 PANEL 150

2.6.3 PANEL 160

PHOTOS OF PANEL 160 AND STAGGERD CORNER

2.6.4 SECTION THROUGH PANELS 101, 150, 160

2.6.5 PERSPECTIVE OF THRU-PANEL CORNER DETAIL – PANEL 101 SHOWN

2.6.6 PERSPECTIVE OF STAGGERED CORNER DETAIL – PANEL 101 SHOWN

2.6.7 RUSTICATED PANEL DETAIL (INTERIOR AND EXTERIOR)

2.7 – ALC SOLUTION PAVERS AND OTHER FLOORING

2.7.1 FD-1 CARREAUX D'OCTAGONES

2.7.2 FD-2 ALTERNATING STEP

2.7.3 FD-3 ALTERNATING RUNNING BOND

2.7.4 FD-4 BASKET WEAVE

2.7.5 FD-5 FORMAL RANDOM

2.7.6 FD-6 HERRINGBONE

2.7.7 FD-7 AMERICAN POPPY

2.7.8 FD-8 ALTERNATING BASKET WEAVE

2.7.9 FD-9 FONTAINEBLEAU PATTERN

2.7.10 FD-10 CHATEAU PATTERN

2.8 – ALC SOLUTION INTERIOR APPLICATIONS

2.8.1 WC-1 WAINSCOT – PANEL 150 AND PROFILES  
230-M AND 220-T SHOWN

2.9 – ALC SOLUTION STANDARD BALUSTRADES

2.9.1 B1 AND B2 STANDARD BALUSTERS  
WITH PROFILES 850 (TOP RAIL) AND 801 (BOTTOM RAIL)  
PHOTO OF B1 BALUSTRADE

## CHAPTER 3. – ALC SOLUTION SYSTEMS AND GUIDES

### 3.1 – ANCHORING SYSTEM, PLANNING AND INSTALLATION GUIDE

- 3.1.1 DOUBLE AND SINGLE ANCHOR  
PHOTOS OF "J" AND "T" ANCHORS AND CUTTING PROCESS
- 3.1.2 REQUIRED ANCHOR WIDTH AND DEADWEIGHT
- 3.1.2A REQUIRED ANCHOR WIDTHS AND STONE SLOT STRENGTHS
- 3.1.3 TYPICAL JOINT AT ANCHOR
- 3.1.4 TYPICAL WALL INSTALLATION – OPTION 1  
PHOTOS OF INDIVIDUAL ANCHOR INSTALLATION
- 3.1.5 TYPICAL WALL INSTALLATION – OPTION 2  
PHOTOS OF CONTINUOUS ANCHOR INSTALLATION
- 3.1.5A INTERMEDIATE STONE ANCHOR DETAIL AT CONCRETE BACK-UP
- 3.1.5B INTERMEDIATE STONE ANCHOR DETAIL AT CMU BLOCK BACK-UP
- 3.1.5C INTERMEDIATE STONE ANCHOR DETAIL AT METAL STUD BACK-UP
- 3.1.6 STONE ANCHOR ARRANGEMENT AT WINDOW
- 3.1.7 STONE ANCHOR ARRANGEMENT AT WINDOW ARCH
- 3.1.8 ISOMETRIC AT BASE AND WINDOW
- 3.1.9 STONE CLADDING BASE
- 3.1.10 DOOR DETAIL AT HEADER
- 3.1.11 DOOR PLANNING GUIDE
- 3.1.12 FLOOR PLANNING GUIDE – PANELS 101 AND 150 SHOWN
- 3.1.13 PLAN SECTION AT CORNER
- 3.1.14 PLAN SECTION AT CORNER – PANEL 101 SHOWN
- 3.1.15 PLAN OF QUOINED CORNER – PANELS 120 AND 121 SHOWN
- 3.1.16 TUSCAN PLAN CORNER DETAIL – QUOIN 126 SHOWN
- 3.1.17 CROSS SECTION AT CORNER – QUOIN 126 SHOWN
- 3.1.18 WINDOW ELEVATION 1
- 3.1.19 WINDOW SECTION 1
- 3.1.20 WINDOW ELEVATION 2
- 3.1.21 WINDOW SECTION 2
- 3.1.22 WINDOW PLANNING GUIDE
- 3.1.23 PROFILE 250-M USED AS WINDOW SILL
- 3.1.24 TUSCAN ENTABLATURE WITH CONCEALED GUTTER – SECTION
- 3.1.25 TUSCAN ENTABLATURE WITH EXPOSED GUTTER (OPT. 1) – SECTION
- 3.1.26 TUSCAN ENTABLATURE WITH EXPOSED GUTTER (OPT.2) – SECTION
- 3.1.27 TUSCAN WATER TABLE – ELEVATION
- 3.1.28 TUSCAN WATER TABLE – SECTION

- 3.2 – ALC SOLUTION INSTALLATION INSTRUCTIONS
  - 3.2.1 INSTALLATION – SUPPLIES AND RECOMMENDED TOOLS
  - 3.2.2 CONTINUOUS BASE ANCHOR INSTALLATION
  - 3.2.3 INDIVIDUAL (CLIP) ANCHOR INSTALLATION
  - 3.2.4 CONTINUOUS ANCHOR INSTALLATION
  - 3.2.5 CONTINUOUS ANCHOR INSTALLATION (CONT'D)
  - 3.2.6 REMOVAL OF PANEL TO BE REPLACED
  - 3.2.7 REMOVAL OF LOWER FLANGE OF UPPER ANCHOR
  - 3.2.8 REPLACEMENT OF PANEL
  
- 3.3 – LIGHT GAUGE STEEL PANEL SYSTEM USING THE ALC SOLUTION
  - 3.3.1 COVER SHEET
  - 3.3.2 MATERIAL DESCRIPTION
  - 3.3.3 CURTAIN WALL SYSTEM
  - 3.3.4 TYPICAL PANEL LAYOUT
  - 3.3.5 SECTION DETAIL AT BASE OF GLAZING
  - 3.3.6 SECTION DETAIL AT JOINT OF STONE PANELING
  - 3.3.7 SECTION DETAIL AT TOP OF GLAZING
  - 3.3.8 SECTION DETAIL OF STRUCTURAL FRAMING
  - 3.3.9 DETAIL AT TOP OF GLAZING
  - 3.3.10 DETAIL AT BASE OF GLAZING
  - 3.3.11 WATER CONTROL DETAIL
  - 3.3.12 SUMMARY OF CURTAIN WALL ERECTION

## CHAPTER 4. – DOCUMENTS AND INFORMATION

- 4.1 – ALC SOLUTION FIVE YEAR LIMITED WARRANTY
  
- 4.2 – LETTERS ON THE ALC SOLUTION
  - 4.2.1 CDC LETTER – ALC 2000 (SOLUTION)
  - 4.2.2 CDC FAX – UPGRADES DUE TO INCREASED WIND PRESSURE
  - 4.2.3 CDC LETTER – ALUMINUM STONE ANCHORS
  
- 4.3 – TECHNICAL INFORMATION
  - 4.3.1 MIXING AND PATCHING INSTRUCTIONS